Nevada Goldfields Inc.
Barite Hill Project

POB 1530
McCormick, SC 29835
USA Telephone: 864-443-2222
USA Fax: 864-443-2187

November 25, 1998

SCDHEC
Bureau of Water Pollution Control
2600 Bull Street
Columbia, SC 29201
Attn: Bruce Crawford

RE: Barite Hill Project – Ground water results/ third quarter 1998
Permit # 16,225 Condition 3

Dear Bruce,

Enclosed are the results of the ground water samples for the third quarter 1998. The following observations were made:

GW1 – Calcium was 19.7 mg/L vs. a calculated tolerance limit of 13.16 mg/L. Cadmium was 0.110 mg/L vs. a calculated tolerance limit o 0.047 mg/L. Copper was 5.21 mg/L vs. a calculated tolerance limit of 3.26 mg/L Sodium was 54.9 mg/L vs. a calculated tolerance limit of 11.6 mg/L. Zinc was 3.98 mg/L vs. a calculated tolerance limit of 1.83 mg/L. Chloride was 9.03 mg/L vs. a calculated tolerance limit of 6.62 mg/L. Sulfate was 491 mg/L vs. a calculated tolerance limit of 239.3 mg/L. Ammonia was 3.26 mg/L vs. a calculated tolerance limit of 0.556 mg/L. TDS was 632 mg/L vs. a calculated tolerance limit of 230 mg/L. The well was dry after removal of one well casing volume was removed. The samples were collected after the well was allowed to recharge.

GW2 - Copper was 6.06 mg/L vs. a calculated tolerance limit of 1.308 mg/L. Ammonia was 1.85 mg/L vs. a calculated limit of 0.328 mg/L. Manganese was 1.33 mg/L vs. a calculated tolerance limit of 0.83 mg/L. Sodium was 19.2 mg/L vs. a calculated tolerance limit of 14.6 mg/L. Sulfate was 704 mg/L vs. a calculated tolerance limit 212 mg/L. TDS was 868 mg/L vs. a calculated tolerance limit of 431 mg/L. The well was dry after one casing volume was removed. The samples were collected once the well recharged.

GW3 – Alkalinity was 179 mg/L vs. a calculated tolerance limit 121 mg/L. Sulfate was 59.9 mg/L vs. a calculated tolerance limit of 39.7 mg/L. The well was dry after one well casing volume was removed. The samples were collected once the well recharged.

GWH – Sodium was 15.3 vs. a calculated tolerance limit of 6.46 mg/L.

GWI – Sodium was 8.97 mg/L vs. a calculated tolerance limit 7.56 mg/L.

GWJ – All the constituents were within the calculated tolerance limits.

GWK – All the constituents were within the calculated tolerance limits. The well was dry after removal of one well casing volume. The samples were collected once the well recharged.

GWP – All the constituents were within the calculated tolerance limits.

If you have any questions, please contact me at 864 443-2222.

Sincerely,

Scott A. Wilkinson
Project Manager

Cc: Frank Filas; Corporate Environmental Manager

file:scdhebc112598

GW Wells Monitoring Report
Third Quarter 1998

NEVADA GOLDFIELDS
McCormick, SC

SIGNATURE PAGE

This report, "Groundwater Sampling and Analytical Procedures Report for Third Quarter, 1998," has been prepared in accordance with accepted quality control practices at the request of and for the exclusive use of **NEVADA GOLDFIELDS** The report has been reviewed by the undersigned reviewers.

SHEALY ENVIRONMENTAL SERVICES, INC.



Michael A. Woodrum, Vice President of Analytical Services
October 28, 1998

Andy Norris, Quality Assurance/Quality Control Officer
October 28, 1998

TABLE OF CONTENTS

GROUNDWATER SAMPLING AND ANALYTICAL PROCEDURES REPORT

Third Quarter 1998

NEVADA GOLDFIELDS, INC.
McCormick, SC

I. INTRODUCTION

This report describes the procedures followed by **SHEALY ENVIRONMENTAL SERVICES, INC. (SHEALY)** during the sampling and analysis of groundwater at **NEVADA GOLDFIELDS,** McCormick, SC. The report includes procedures for:

1. Sample collection
2. Sample preservation
3. Chain-of-Custody control
4. Analytical protocol

These procedures were developed by **SHEALY** to comply with the sampling procedures recommended by SCDHEC, the US Environmental Protection Agency (EPA), the Resource Conservation and Recovery Act (RCRA), Groundwater Monitoring Technical Enforcement Guidance Document (TEGD) (1986), and published research findings. The protocol described was designed to insure that the integrity of the samples were maintained in the field, during transit to the laboratory and throughout the analytical procedures.

I.A. MONITORING PARAMETERS AND FREQUENCY

The following wells were sampled during August 1998:

GW-1	GW-2	GW-3	Well K
Well J	Well H	Well P	Well I

These monitoring wells were analyzed for the following parameters:

*TDS * Nitrate-N * Nitrite-N * Alkalinity-Bicarbonate
*Sulfate *Chloride *TOC * Ammonia * Cyanide
*Metals: As,Hg,Se,Pb,Al,Ba,Cd,Ca,Cr,Cu,Fe,Mg,Mn,Ni,K,Ag,Na,Zn
Dissolved Cu

I.B. SAMPLING PROTOCOL

The procedures described below are intended to insure that representative groundwater samples are collected. Procedures for measurement of the water table depth, measurement of total well depth, well evacuation, and sample collection are included.

For each well, all data collected were recorded on a Field Data Information Sheet. Prior to the initiation of activities at each well, all sampling personnel put on new, laboratory quality PVC gloves. These gloves were replaced as necessary during the well evacuation and sampling procedure. Prior to the collection of any groundwater quality data at each well, the surface integrity of the well was checked. Any problems which could affect groundwater sample integrity were noted on the Field Data Information Sheet.

I.B.1. Water Level Measurement

Prior to the evacuation of each monitoring well, the depth to the water table was determined with the use of an electronic water level indicator. The water level indicator uses a sensitive circuitry to activate a buzzer when electrical continuity is made at the probe. The sensitivity is set so that waters with conductivities greater than approximately one umhos/cm will close the circuit. After use at each well, the instrument was cleaned according to the "Field Cleaning Procedures," which are described in Section I.C.1. The depth to the water table was measured by turning the instrument on and then slowly lowering the instrument probe into the well until the buzzer sounded. The distance from the measuring point of the well to the water level was then measured and recorded. The instrument was calibrated in 0.05 foot increments. All measurements were made and estimated to the nearest 0.01 foot.

I.B.2. Total Depth Measurement

The total depth measurement is used in calculating the volume of water standing in the well casing. The total well depth was taken from historical data.

I.B.3. Well Evacuation

The purpose of the well evacuation procedure is to initiate the introduction of water from the surrounding aquifer into which the well is placed. By removing standing water from the well, a hydraulic gradient is created which results in water from the surrounding aquifer into the well. The quality of this water is representative of the water quality immediately surrounding the well.

Well evacuation and sampling of all wells at the site were done using 1.66 inch outside diameter, three foot long Teflon or stainless steel bailers with a single bottom check valve. All bailers were cleaned at the laboratory prior to use, and a separate bailer was used for each well. When field cleaning was required, the method outlined in Section I.C.1. was used and new 1/8 inch nylon twine was used for each well.

The following steps were followed for evacuation with Teflon bailers:

1. The depth to the water table was subtracted from the total well depth to determine the length of the water column. The water column length was multiplied by the appropriate conversion factor for that particular well casing diameter to determine the volume, in gallons, of water standing in the well casing. This volume was then multiplied by three to calculate the standard evacuation volume.
2. The bailer was lowered to a depth just below the water level in the well each time to insure adequate evacuation of the standing water.
3. The pH and Specific Conductivity were measured and recorded periodically during well evacuation. For high yield wells, well evacuation continued until the standard evacuation volume was removed and both pH and Specific Conductivity were relatively stable. Stability of the pH is defined as two consecutive measurements varying by no more than 10 percent. All evacuated volumes and field measurements were recorded on the Field Data Information Sheet.

Wells which were evacuated to dryness prior to reaching the standard evacuation volume were sampled as soon as a sufficient volume of water had entered the well. Field parameters were measured prior to sample collection to insure water quality stability.

I.B.4. <u>Sample Collection</u>

The primary consideration during the collection of groundwater samples is to insure that the sample is not altered or contaminated during withdrawal from the well and introduction into the sample container.

A complete set of pre-cleaned and pre-labeled sample containers were removed from the cooler and slowly filled with fresh sample, poured directly from the bailer. Preservatives were added to the sample bottles prior to leaving for the sampling event. Care was taken to insure that the bailer did not contact the sample bottle during filling. The filled bottles were then capped and securely placed into the pre-cleaned cooler. The Chain of Custody Form, was then completed for that well. Finally, the well was re-capped and locked.

I.C. FIELD QUALITY CONTROL

A strict quality control program is followed in the field by **SHEALY** to insure that sample integrity is maintained during sample collection and transit to the laboratory. In addition, all equipment and instruments are carefully maintained and calibrated in accordance with schedules and procedures described in SHEALY's Quality Control Manual entitled "SOP and QA Manual for Groundwater Sampling".

I.C.1. Field Cleaning Procedures

All field equipment and instrumentation are cleaned at the laboratory according to standard laboratory procedures upon return from each sampling trip. Field equipment and instrumentation include: sample coolers, pH and Specific Conductivity meters, and field measurement vessels. If instrumentation and field equipment were used on more than one well, it was cleaned according to the following field cleaning procedures:

1. Rinse item thoroughly with a 5% phosphate-free laboratory detergent solution.
2. Rinse item with deionized water, twice.

I.C.2. Field Instruments and Measuring Devices

Instruments and devices used to collect field data at the **NEVADA GOLDFIELDS** facility include: pH and Specific Conductivity meters and an electronic water level indicator.

The pH and Specific Conductivity meters were calibrated in the field prior to sampling. The pH meter was calibrated using a 4 SU standard and a 10 SU standard. The Specific Conductivity meter was also calibrated in the field according to SHEALY's Field Operation SOP and the manufacturer's specifications. All calibration records for both meters are recorded in the appropriate calibration log books maintained at Shealy.

I.C.3. Field Blanks

One set of field blanks was collected during the sampling event. At that time, one set of bottles was randomly removed from the sample cooler and labeled as "Field Blank". The Field Blank was obtained by filling a laboratory cleaned bailer with deionized water. this water was then poured into the labeled sample bottles. The deionized water is also used to rinse field equipment. Once filled, the field blanks were treated as samples and placed in the sample cooler for transport to the laboratory. Field blanks and groundwater samples were analyzed for the same parameters in order to assure quality control during sampling, transportation, and analysis.

I.C.4. Field Data Information Sheet

All pertinent field information was recorded on the Field Data Information Sheet as it was collected. This information includes: date of sampling, name of collector, monitoring well number, casing diameter and material of construction, well integrity, measuring point elevation, total well depth, depth to groundwater, volume of water in casing, method of evacuation and sampling, total volume of water evacuated, field measurements with time and volume evacuated, and field observations. Information on the Field Data Information Sheets was reviewed upon arrival at the laboratory and pertinent information transferred to the Certificate of analysis and noted as field measurements.

I.C.5. Sample Transportation and Chain of Custody

The transportation of groundwater samples from the time of collection to their arrival at the laboratory is an important part of the groundwater monitoring program. The mode of travel must be such that the sample is not altered physically, chemically, or biologically. The travel time to the laboratory must not interfere with the sample holding time. The Chain of Custody must also be maintained during the transportation process. Samples collected at the **NEVADA GOLDFIELDS** facility remained in the possession of **SHEALY** personnel and were transported to the laboratory within the allowed holding time of all the required parameters. Custody is defined as:

1. Being in one's physical possession.
2. Being in one's view, after being in one's possession.
3. Being in a designated secure area.

Upon arrival at the laboratory, the sampling personnel relinquished the samples to the laboratory sample custodian. This transaction was documented on the Chain of Custody Form.

Reviewed By: _____ 10/23/98

Milton P. Quattlebaum — Date

Field Service Supervisor

II. ANALYTICAL PROTOCOL

The analytical protocols used at SHEALY to insure that groundwater quality at the **NEVADA GOLDFIELDS** facility was accurately detected and quantified were taken two EPA sources, Methods for Chemical Analyses of Water and Wastes and Test Methods for Evaluation Solid Waste. The analysis for metals was for the total recoverable fraction. Laboratory Quality Control/Quality Assurance procedures are presented in detail in the SHEALY's SOP Manuals.

SHEALY ENVIRONMENTAL SERVICES, INC.

Scientists and Consultants

106 VANTAGE POINT DRIVE
CAYCE, SOUTH CAROLINA 29033

(803) 791-9700
FAX (803) 791-9111
www.shealyenvironmental.com

CERTIFICATE OF ANALYSIS

SC DHEC No. 32010

NC DEHNR No. 329

Client: NEVADA GOLDFIELDS
P.O. Box 1530
McCormick, SC 29835

Attention: Scott Wilkinson

SHEALY Lab No: 147431
Description: GW-1

Coll. Date: 09/25/98
Coll. Time:

Date Received: 09/25/98
Date Reported: 10/28/98
Date Revised: 11/23/98

QA/QC Officer _____

V.P. Analytical _____

Parameters	Method	Result	Units	Date Prepared	Date Analyzed	Anal.
Well Depth		36.95	ft.		09/25/98	GWS
Water Level Depth From Top of Casing		24.95	ft.		09/25/98	GWS
pH-Field at 17.0 C	150.1	3.68	SU		09/25/98	GWS
Specific Conductance at 25 C - Field	120.1	448	umhos/cm		09/25/98	GWS
Temperature-Field	170.1	17.0	C		09/25/98	GWS
INORGANICS						
Alkalinity-Bicarbonate	SM4500D	16.2	mg/l		09/28/98	NWD
Ammonia-N	350.3	3.26	mg/l	09/29/98	09/29/98	EDN
Chloride	300.0	9.03	mg/l		09/28/98	JPS
Cyanide-Total	335.2	<0.010	mg/l	09/29/98	09/30/98	JDH
Nitrate-N	353.2	0.568	mg/l		09/25/98	NWD
Nitrite-N	354.1	0.065	mg/l		09/25/98	NWD
Sulfate	300.0	491	mg/l		10/02/98	JPS
TOC	415.1	3.4	mg/l		10/01/98	JPS
TDS	160.1	632	mg/l		09/29/98	JEM
METALS						
Aluminum	6010B	13.8	mg/l	10/02/98	10/08/98	FTS
Arsenic	6010B	0.006	mg/l	10/02/98	10/08/98	FTS
Barium	6010B	0.098	mg/l	10/02/98	10/08/98	FTS
Cadmium	6010B	0.110	mg/l	10/02/98	10/08/98	FTS
Calcium	6010B	19.7	mg/l	10/02/98	10/08/98	FTS
Chromium	6010B	0.005	mg/l	10/02/98	10/08/98	FTS
Copper	6010B	5.21	mg/l	10/09/98	10/12/98	FTS
Iron	200.7	57.7	mg/l	10/02/98	10/08/98	FTS
Lead	6010B	<0.003	mg/l	10/02/98	10/08/98	FTS
Magnesium	6010B	14.5	mg/l	10/02/98	10/08/98	FTS
Manganese	6010B	2.79	mg/l	10/02/98	10/08/98	FTS
Mercury	7470A	0.006	mg/l	09/30/98	10/01/98	FTC
Nickel	6010B	0.077	mg/l	10/02/98	10/08/98	FTS
Potassium	6010B	1.45	mg/l	10/02/98	10/08/98	FTS
Selenium	6010B	0.014	mg/l	10/02/98	10/08/98	FTS
Silver	6010B	<0.005	mg/l	10/02/98	10/09/98	FTS
Sodium	6010B	54.9	mg/l	10/02/98	10/08/98	FTS
Zinc	6010B	3.98	mg/l	10/02/98	10/08/98	FTS
Dissolved Copper	6010B	4.48	mg/l	10/09/98	10/12/98	FTS

SHEALY ENVIRONMENTAL SERVICES, INC.

Scientists and Consultants

106 VANTAGE POINT DRIVE
CAYCE, SOUTH CAROLINA 29033

(803) 791-9700
FAX (803) 791-9111
www.shealyenvironmental.com

CERTIFICATE OF ANALYSIS

SC DHEC No. 32010

NC DEHNR No. 329

Client: NEVADA GOLDFIELDS
P.O. Box 1530
McCormick, SC 29835

Attention: Scott Wilkinson

SHEALY Lab No: 147432
Description: GW-2

Coll. Date: 09/25/98
Coll. Time:

Date Received: 09/25/98
Date Reported: 10/28/98
Date Revised: 11/23/98

QA/QC Officer _____

V.P. Analytical _____

Parameters	Method	Result	Units	Date Prepared	Date Analyzed	Anal.
Well Depth		28.20	ft.		09/25/98	GWS
Water Level Depth From Top of Casing		22.50	ft.		09/25/98	GWS
pH-Field at 18.0 C	150.1	3.62	SU		09/25/98	GWS
Specific Conductance at 25 C - Field	120.1	750	umhos/cm		09/25/98	GWS
Temperature-Field	170.1	18.0	C		09/25/98	GWS
INORGANICS						
Alkalinity-Bicarbonate	SM4500D	17.8	mg/l		09/28/98	NWD
Ammonia-N	350.3	1.85	mg/l	09/29/98	09/29/98	EDN
Chloride	300.0	4.90	mg/l		09/28/98	JPS
Cyanide-Total	335.2	<0.010	mg/l	09/29/98	09/30/98	JDH
Nitrate-N	353.2	<0.020	mg/l		09/25/98	NWD
Nitrite-N	354.1	<0.020	mg/l		09/25/98	NWD
Sulfate	300.0	704	mg/l		10/02/98	JPS
TOC	415.1	1.2	mg/l		10/01/98	JPS
TDS	160.1	868	mg/l		09/29/98	JEM
METALS						
Aluminum	6010B	7.07	mg/l	10/02/98	10/08/98	FTS
Arsenic	6010B	<0.005	mg/l	10/02/98	10/08/98	FTS
Barium	6010B	0.0225	mg/l	10/02/98	10/08/98	FTS
Cadmium	6010B	0.071	mg/l	10/02/98	10/08/98	FTS
Calcium	6010B	37.5	mg/l	10/02/98	10/08/98	FTS
Chromium	6010B	<0.005	mg/l	10/02/98	10/08/98	FTS
Copper	6010B	6.06	mg/l	10/09/98	10/12/98	FTS
Iron	200.7	110	mg/l	10/02/98	10/08/98	FTS
Lead	6010B	<0.003	mg/l	10/02/98	10/08/98	FTS
Magnesium	6010B	8.93	mg/l	10/02/98	10/08/98	FTS
Manganese	6010B	1.33	mg/l	10/02/98	10/08/98	FTS
Mercury	7470A	<0.0001	mg/l	09/30/98	10/01/98	FTC
Nickel	6010B	0.113	mg/l	10/02/98	10/08/98	FTS
Potassium	6010B	2.28	mg/l	10/02/98	10/08/98	FTS
Selenium	6010B	0.009	mg/l	10/02/98	10/08/98	FTS
Silver	6010B	<0.005	mg/l	10/02/98	10/09/98	FTS
Sodium	6010B	19.2	mg/l	10/02/98	10/08/98	FTS
Zinc	6010B	3.21	mg/l	10/02/98	10/08/98	FTS
Dissolved Copper	6010B	6.28	mg/l	10/09/98	10/12/98	FTS

SHEALY ENVIRONMENTAL SERVICES, INC.

Scientists and Consultants

106 VANTAGE POINT DRIVE
CAYCE, SOUTH CAROLINA 29033

(803) 791-9700
FAX (803) 791-9111
www.shealyenvironmental.com

CERTIFICATE OF ANALYSIS

SC DHEC No. 32010

NC DEHNR No. 329

Client: NEVADA GOLDFIELDS
P.O. Box 1530
McCormick, SC 29835

Attention: Scott Wilkinson

SHEALY Lab No: 147433
Description: GW-3

Coll. Date: 09/25/98
Coll. Time:

Date Received: 09/25/98
Date Reported: 10/28/98
Date Revised: 11/23/98

QA/QC Officer

V.P. Analytical

Parameters	Method	Result	Units	Date Prepared	Date Analyzed	Anal.
Well Depth		22.6	ft.		09/25/98	GWS
Water Level Depth From Top of Casing		11.4	ft.		09/25/98	GWS
pH-Field at 19.0 C	150.1	6.17	SU		09/25/98	GWS
Specific Conductance at 25 C - Field	120.1	232	umhos/cm		09/25/98	GWS
Temperature-Field	170.1	19.0	C		09/25/98	GWS
INORGANICS						
Alkalinity-Bicarbonate	SM4500D	179	mg/l		09/28/98	NWD
Ammonia-N	350.3	0.126	mg/l	09/29/98	09/29/98	EDN
Chloride	300.0	4.27	mg/l		09/28/98	JPS
Cyanide-Total	335.2	<0.010	mg/l	09/29/98	09/30/98	JDH
Nitrate-N	353.2	<0.020	mg/l		09/25/98	NWD
Nitrite-N	354.1	<0.020	mg/l		10/02/98	NWD
Sulfate	300.0	59.9	mg/l		10/02/98	JPS
TOC	415.1	1.1	mg/l		10/01/98	JPS
TDS	160.1	248	mg/l		09/29/98	JEM
METALS						
Aluminum	6010B	30.6	mg/l	10/02/98	10/08/98	FTS
Arsenic	6010B	<0.005	mg/l	10/02/98	10/08/98	FTS
Barium	6010B	0.054	mg/l	10/02/98	10/08/98	FTS
Cadmium	6010B	<0.002	mg/l	10/02/98	10/08/98	FTS
Calcium	6010B	23.6	mg/l	10/02/98	10/08/98	FTS
Chromium	6010B	0.038	mg/l	10/02/98	10/08/98	FTS
Copper	6010B	0.127	mg/l	10/02/98	10/08/98	FTS
Iron	200.7	45.2	mg/l	10/02/98	10/08/98	FTS
Lead	6010B	<0.003	mg/l	10/02/98	10/08/98	FTS
Magnesium	6010B	45.1	mg/l	10/02/98	10/08/98	FTS
Manganese	6010B	2.12	mg/l	10/02/98	10/08/98	FTS
Mercury	7470A	<0.0001	mg/l	09/30/98	10/01/98	FTC
Nickel	6010B	0.027	mg/l	10/02/98	10/08/98	FTS
Potassium	6010B	0.390	mg/l	10/02/98	10/08/98	FTS
Selenium	6010B	<0.005	mg/l	10/02/98	10/08/98	FTS
Silver	6010B	<0.005	mg/l	10/02/98	10/09/98	FTS
Sodium	6010B	10.7	mg/l	10/02/98	10/08/98	FTS
Zinc	6010B	0.367	mg/l	10/02/98	10/08/98	FTS
Dissolved Copper	6010B	0.024	mg/l	10/02/98	10/08/98	FTS

SHEALY ENVIRONMENTAL SERVICES, INC.

Scientists and Consultants

106 VANTAGE POINT DRIVE
CAYCE, SOUTH CAROLINA 29033

(803) 791-9700
FAX (803) 791-9111
www.shealyenvironmental.com

CERTIFICATE OF ANALYSIS

SC DHEC No. 32010

NC DEHNR No. 329

Client: NEVADA GOLDFIELDS
P.O. Box 1530
McCormick, SC 29835

Attention: Scott Wilkinson

SHEALY Lab No: 147437
Description: Well H

Coll. Date: 09/25/98
Coll. Time: 1320

Date Received: 09/25/98
Date Reported: 10/28/98
Date Revised: 11/23/98

QA/QC Officer _____

V.P. Analytical _____

Parameters	Method	Result	Units	Date Prepared	Date Analyzed	Anal.
Well Depth		61.98	ft.		09/25/98	GWS
Water Level Depth From Top of Casing		51.91	ft.		09/25/98	GWS
pH-Field at 19.0 C	150.1	4.63	SU		09/25/98	GWS
Specific Conductance at 25 C - Field	120.1	90.4	umhos/cm		09/25/98	GWS
Temperature-Field	170.1	19.0	C		09/25/98	GWS
INORGANICS						
Alkalinity-Bicarbonate	SM4500D	<10.0	mg/l		09/28/98	NWD
Ammonia-N	350.3	0.131	mg/l	09/29/98	09/29/98	EDN
Chloride	300.0	6.64	mg/l		09/28/98	JPS
Cyanide-Total	335.2	<0.010	mg/l	09/29/98	09/30/98	JDH
Nitrate-N	353.2	2.30	mg/l		09/25/98	NWD
Nitrite-N	354.1	<0.020	mg/l		09/25/98	NWD
Sulfate	300.0	19.5	mg/l		09/28/98	JPS
TOC	415.1	1.1	mg/l		10/01/98	JPS
TDS	160.1	120	mg/l		09/29/98	JEM
METALS						
Aluminum	6010B	0.334	mg/l	10/02/98	10/08/98	FTS
Arsenic	6010B	<0.005	mg/l	10/02/98	10/08/98	FTS
Barium	6010B	0.026	mg/l	10/02/98	10/08/98	FTS
Cadmium	6010B	<0.002	mg/l	10/02/98	10/08/98	FTS
Calcium	6010B	1.43	mg/l	10/02/98	10/08/98	FTS
Chromium	6010B	<0.005	mg/l	10/02/98	10/08/98	FTS
Copper	6010B	0.041	mg/l	10/02/98	10/08/98	FTS
Iron	200.7	3.16	mg/l	10/02/98	10/08/98	FTS
Lead	6010B	<0.003	mg/l	10/02/98	10/08/98	FTS
Magnesium	6010B	<5.00	mg/l	10/02/98	10/08/98	FTS
Manganese	6010B	0.110	mg/l	10/02/98	10/08/98	FTS
Mercury	7470A	<0.0001	mg/l	09/30/98	10/01/98	FTC
Nickel	6010B	<0.010	mg/l	10/02/98	10/08/98	FTS
Potassium	6010B	0.274	mg/l	10/02/98	10/08/98	FTS
Selenium	6010B	<0.005	mg/l	10/02/98	10/08/98	FTS
Silver	6010B	<0.005	mg/l	10/02/98	10/09/98	FTS
Sodium	6010B	15.3	mg/l	10/02/98	10/08/98	FTS
Zinc	6010B	0.036	mg/l	10/02/98	10/08/98	FTS
Dissolved Copper	6010B	0.017	mg/l	10/02/98	10/08/98	FTS

SHEALY ENVIRONMENTAL SERVICES, INC.

Scientists and Consultants

106 VANTAGE POINT DRIVE
CAYCE, SOUTH CAROLINA 29033

(803) 791-9700
FAX (803) 791-9111
www.shealyenvironmental.com

CERTIFICATE OF ANALYSIS

SC DHEC No. 32010

NC DEHNR No. 329

Client: NEVADA GOLDFIELDS
P.O. Box 1530
McCormick, SC 29835

Attention: Scott Wilkinson

SHEALY Lab No: 147438
Description: Well I

Coll. Date: 09/25/98
Coll. Time: 1345

Date Received: 09/25/98
Date Reported: 10/28/98
Date Revised: 11/23/98

QA/QC Officer MA

V.P. Analytical MA

Parameters	Method	Result	Units	Date Prepared	Date Analyzed	Anal.
Well Depth		88.30	ft.		09/25/98	GWS
Water Level Depth From Top of Casing		52.25	ft.		09/25/98	GWS
pH-Field at 20.0 C	150.1	4.55	SU		09/25/98	GWS
Specific Conductance at 25 C - Field	120.1	71.9	umhos/cm		09/25/98	GWS
Temperature-Field	170.1	20.0	C		09/25/98	GWS
INORGANICS						
Alkalinity-Bicarbonate	SM4500D	<10.0	mg/l		09/28/98	NWD
Ammonia-N	350.3	0.106	mg/l	09/29/98	09/29/98	EDN
Chloride	300.0	9.06	mg/l		09/28/98	JPS
Cyanide-Total	335.2	0.022	mg/l	09/29/98	09/30/98	JDH
Nitrate-N	353.2	1.32	mg/l		09/25/98	NWD
Nitrite-N	354.1	<0.020	mg/l		09/25/98	NWD
Sulfate	300.0	11.5	mg/l		09/28/98	JPS
TOC	415.1	<1.0	mg/l		10/01/98	JPS
TDS	160.1	152	mg/l		09/29/98	JEM
METALS						
Aluminum	6010B	0.448	mg/l	10/02/98	10/08/98	FTS
Arsenic	6010B	<0.005	mg/l	10/02/98	10/08/98	FTS
Barium	6010B	0.033	mg/l	10/02/98	10/08/98	FTS
Cadmium	6010B	<0.002	mg/l	10/02/98	10/08/98	FTS
Calcium	6010B	1.52	mg/l	10/02/98	10/08/98	FTS
Chromium	6010B	0.008	mg/l	10/02/98	10/08/98	FTS
Copper	6010B	0.009	mg/l	10/02/98	10/08/98	FTS
Iron	200.7	0.570	mg/l	10/02/98	10/08/98	FTS
Lead	6010B	<0.003	mg/l	10/02/98	10/08/98	FTS
Magnesium	6010B	2.36	mg/l	10/02/98	10/08/98	FTS
Manganese	6010B	0.058	mg/l	10/02/98	10/08/98	FTS
Mercury	7470A	0.0005	mg/l	09/30/98	10/01/98	FTC
Nickel	6010B	<0.010	mg/l	10/02/98	10/08/98	FTS
Potassium	6010B	0.264	mg/l	10/02/98	10/08/98	FTS
Selenium	6010B	<0.005	mg/l	10/02/98	10/08/98	FTS
Silver	6010B	<0.005	mg/l	10/02/98	10/09/98	FTS
Sodium	6010B	8.97	mg/l	10/02/98	10/08/98	FTS
Zinc	6010B	0.018	mg/l	10/02/98	10/08/98	FTS
Dissolved Copper	6010B	<0.005	mg/l	10/02/98	10/08/98	FTS

SHEALY ENVIRONMENTAL SERVICES, INC.

Scientists and Consultants

106 VANTAGE POINT DRIVE
CAYCE, SOUTH CAROLINA 29033

(803) 791-9700
FAX (803) 791-9111
www.shealyenvironmental.com

CERTIFICATE OF ANALYSIS

SC DHEC No. 32010

NC DEHNR No. 329

Client: NEVADA GOLDFIELDS
P.O. Box 1530
McCormick, SC 29835

Attention: Scott Wilkinson

SHEALY Lab No: 147436
Description: Well J

Coll. Date: 09/25/98
Coll. Time: 1300

Date Received: 09/25/98
Date Reported: 10/28/98
Date Revised: 11/23/98

QA/QC Officer _____

V.P. Analytical _____

Parameters	Method	Result	Units	Date Prepared	Date Analyzed	Anal.
Well Depth		63.90	ft.		09/25/98	GWS
Water Level Depth From Top of Casing		58.65	ft.		09/25/98	GWS
pH-Field at 19.0 C	150.1	5.11	SU		09/25/98	GWS
Specific Conductance at 25 C - Field	120.1	79.1	umhos/cm		09/25/98	GWS
Temperature-Field	170.1	19.0	C		09/25/98	GWS
INORGANICS						
Alkalinity-Bicarbonate	SM4500D	10.3	mg/l		09/28/98	NWD
Ammonia-N	350.3	0.112	mg/l	09/29/98	09/29/98	EDN
Chloride	300.0	4.24	mg/l		09/28/98	JPS
Cyanide-Total	335.2	<0.010	mg/l	09/29/98	09/30/98	JDH
Nitrate-N	353.2	0.694	mg/l		09/25/98	NWD
Nitrite-N	354.1	<0.020	mg/l		09/25/98	NWD
Sulfate	300.0	19.6	mg/l		09/28/98	JPS
TOC	415.1	<1.0	mg/l		10/01/98	JPS
TDS	160.1	132	mg/l		09/29/98	JEM
METALS						
Aluminum	6010B	0.707	mg/l	10/02/98	10/08/98	FTS
Arsenic	6010B	<0.005	mg/l	10/02/98	10/08/98	FTS
Barium	6010B	0.017	mg/l	10/02/98	10/08/98	FTS
Cadmium	6010B	<0.002	mg/l	10/02/98	10/08/98	FTS
Calcium	6010B	2.27	mg/l	10/02/98	10/08/98	FTS
Chromium	6010B	<0.005	mg/l	10/02/98	10/08/98	FTS
Copper	6010B	0.023	mg/l	10/02/98	10/08/98	FTS
Iron	200.7	3.80	mg/l	10/02/98	10/08/98	FTS
Lead	6010B	<0.003	mg/l	10/02/98	10/08/98	FTS
Magnesium	6010B	3.93	mg/l	10/02/98	10/08/98	FTS
Manganese	6010B	0.064	mg/l	10/02/98	10/08/98	FTS
Mercury	7470A	<0.0001	mg/l	09/30/98	10/01/98	FTC
Nickel	6010B	<0.010	mg/l	10/02/98	10/08/98	FTS
Potassium	6010B	0.268	mg/l	10/02/98	10/08/98	FTS
Selenium	6010B	<0.005	mg/l	10/02/98	10/08/98	FTS
Silver	6010B	<0.005	mg/l	10/02/98	10/09/98	FTS
Sodium	6010B	6.49	mg/l	10/02/98	10/08/98	FTS
Zinc	6010B	0.026	mg/l	10/02/98	10/08/98	FTS
Dissolved Copper	6010B	<0.005	mg/l	10/02/98	10/08/98	FTS

SHEALY ENVIRONMENTAL SERVICES, INC.

Scientists and Consultants

106 VANTAGE POINT DRIVE
CAYCE, SOUTH CAROLINA 29033

(803) 791-9700
FAX (803) 791-9111
www.shealyenvironmental.com

CERTIFICATE OF ANALYSIS

SC DHEC No. 32010

NC DEHNR No. 329

Client: NEVADA GOLDFIELDS
P.O. Box 1530
McCormick, SC 29835

Attention: Scott Wilkinson

SHEALY Lab No: 147435
Description: Well K

Coll. Date: 09/25/98
Coll. Time: 1210

Date Received: 09/25/98
Date Reported: 10/28/98
Date Revised: 11/23/98

QA/QC Officer

V.P. Analytical

Parameters	Method	Result	Units	Date Prepared	Date Analyzed	Anal.
Well Depth		82.53	ft.		09/25/98	GWS
Water Level Depth From Top of Casing		60.25	ft.		09/25/98	GWS
pH-Field at 20.0 C	150.1	5.89	SU		09/25/98	GWS
Specific Conductance at 25 C - Field	120.1	88.4	umhos/cm		09/25/98	GWS
Temperature-Field	170.1	20.0	C		09/25/98	GWS
INORGANICS						
Alkalinity-Bicarbonate	SM4500D	39.5	mg/l		09/28/98	NWD
Ammonia-N	350.3	0.992	mg/l	09/29/98	09/29/98	EDN
Chloride	300.0	3.85	mg/l		09/28/98	JPS
Cyanide-Total	335.2	<0.010	mg/l	09/29/98	09/30/98	JDH
Nitrate-N	353.2	0.024	mg/l		09/25/98	NWD
Nitrite-N	354.1	0.080	mg/l		09/25/98	NWD
Sulfate	300.0	4.51	mg/l		09/28/98	JPS
TOC	415.1	<1.0	mg/l		10/01/98	JPS
TDS	160.1	116	mg/l		09/29/98	JEM
METALS						
Aluminum	6010B	35.6	mg/l	10/02/98	10/08/98	FTS
Arsenic	6010B	0.006	mg/l	10/02/98	10/08/98	FTS
Barium	6010B	0.112	mg/l	10/02/98	10/08/98	FTS
Cadmium	6010B	<0.002	mg/l	10/02/98	10/08/98	FTS
Calcium	6010B	9.56	mg/l	10/02/98	10/08/98	FTS
Chromium	6010B	0.055	mg/l	10/02/98	10/08/98	FTS
Copper	6010B	0.091	mg/l	10/02/98	10/08/98	FTS
Iron	200.7	63.6	mg/l	10/02/98	10/08/98	FTS
Lead	6010B	<0.003	mg/l	10/02/98	10/08/98	FTS
Magnesium	6010B	30.9	mg/l	10/02/98	10/08/98	FTS
Manganese	6010B	1.13	mg/l	10/02/98	10/08/98	FTS
Mercury	7470A	<0.0001	mg/l	09/30/98	10/01/98	FTC
Nickel	6010B	0.050	mg/l	10/02/98	10/08/98	FTS
Potassium	6010B	0.343	mg/l	10/02/98	10/08/98	FTS
Selenium	6010B	<0.005	mg/l	10/02/98	10/08/98	FTS
Silver	6010B	<0.005	mg/l	10/02/98	10/09/98	FTS
Sodium	6010B	7.18	mg/l	10/02/98	10/08/98	FTS
Zinc	6010B	0.655	mg/l	10/02/98	10/08/98	FTS
Dissolved Copper	6010B	<0.005	mg/l	10/02/98	10/08/98	FTS

SHEALY ENVIRONMENTAL SERVICES, INC.

Scientists and Consultants

106 VANTAGE POINT DRIVE
CAYCE, SOUTH CAROLINA 29033

(803) 791-9700
FAX (803) 791-9111
www.shealyenvironmental.com

CERTIFICATE OF ANALYSIS

SC DHEC No. 32010

NC DEHNR No. 329

Client: NEVADA GOLDFIELDS
P.O. Box 1530
McCormick, SC 29835

Attention: Scott Wilkinson

SHEALY Lab No: 147434
Description: Well P

Coll. Date: 09/25/98
Coll. Time: 1125

Date Received: 09/25/98
Date Reported: 10/28/98
Date Revised: 11/23/98

QA/QC Officer _____

V.P. Analytical _____

Parameters	Method	Result	Units	Date Prepared	Date Analyzed	Anal.
Well Depth		89.18	ft.		09/25/98	GWS
Water Level Depth From Top of Casing		73.06	ft.		09/25/98	GWS
pH-Field at 19.0 C	150.1	5.99	SU		09/25/98	GWS
Specific Conductance at 25 C - Field	120.1	113	umhos/cm		09/25/98	GWS
Temperature-Field	170.1	19.0	C		09/25/98	GWS
INORGANICS						
Alkalinity-Bicarboante	SM4500D	61.0	mg/l		09/28/98	NWD
Ammonia-N	350.3	0.191	mg/l	10/01/98	10/01/98	JDH
Chloride	300.0	3.41	mg/l		09/28/98	JPS
Cyanide-Total	335.2	<0.010	mg/l	09/29/98	09/30/98	JDH
Nitrate-N	353.2	<0.020	mg/l		09/25/98	NWD
Nitrite-N	354.1	0.032	mg/l		09/25/98	NWD
Sulfate	300.0	5.28	mg/l		09/28/98	JPS
TOC	415.1	<1.0	mg/l		10/01/98	JPS
TDS	160.1	148	mg/l		09/29/98	JEM
METALS						
Aluminum	6010B	8.51	mg/l	10/02/98	10/08/98	FTS
Arsenic	6010B	<0.005	mg/l	10/02/98	10/08/98	FTS
Barium	6010B	0.017	mg/l	10/02/98	10/08/98	FTS
Cadmium	6010B	<0.002	mg/l	10/02/98	10/08/98	FTS
Calcium	6010B	6.35	mg/l	10/02/98	10/08/98	FTS
Chromium	6010B	0.038	mg/l	10/02/98	10/08/98	FTS
Copper	6010B	0.031	mg/l	10/02/98	10/08/98	FTS
Iron	200.7	15.0	mg/l	10/02/98	10/08/98	FTS
Lead	6010B	<0.003	mg/l	10/02/98	10/08/98	FTS
Magnesium	6010B	13.4	mg/l	10/02/98	10/08/98	FTS
Manganese	6010B	0.721	mg/l	10/02/98	10/08/98	FTS
Mercury	7470A	0.0004	mg/l	09/30/98	10/01/98	FTC
Nickel	6010B	0.022	mg/l	10/02/98	10/08/98	FTS
Potassium	6010B	0.294	mg/l	10/02/98	10/08/98	FTS
Selenium	6010B	<0.005	mg/l	10/02/98	10/08/98	FTS
Silver	6010B	<0.005	mg/l	10/02/98	10/09/98	FTS
Sodium	6010B	9.41	mg/l	10/02/98	10/08/98	FTS
Zinc	6010B	0.275	mg/l	10/02/98	10/08/98	FTS
Dissolved Copper	6010B	<0.005	mg/l	10/02/98	10/08/98	FTS

SHEALY ENVIRONMENTAL SERVICES, INC.

Scientists and Consultants

106 VANTAGE POINT DRIVE
CAYCE, SOUTH CAROLINA 29033

(803) 791-9700
FAX (803) 791-9111
www.shealyenvironmental.com

CERTIFICATE OF ANALYSIS

SC DHEC No. 32010

NC DEHNR No. 329

Client: NEVADA GOLDFIELDS
P.O. Box 1530
McCormick, SC 29835

Attention: Scott Wilkinson

SHEALY Lab No: 147439
Description: Field Blank

Coll. Date: 09/25/98
Coll. Time: 1336

Date Received: 09/25/98
Date Reported: 10/28/98
Date Revised: 11/23/98

QA/QC Officer MAP

V.P. Analytical MAP

Parameters	Method	Result	Units	Date Prepared	Date Analyzed	Anal.
INORGANICS						
Alkalinity-Bicarbonate	SM4500D	<10.0	mg/l		09/28/98	NWD
Ammonia-N	350.3	<0.100	mg/l	09/29/98	09/29/98	EDN
Chloride	300.0	<1.00	mg/l		09/28/98	JPS
Cyanide-Total	335.2	<0.010	mg/l	09/29/98	09/30/98	JDH
Nitrate-N	353.2	<0.020	mg/l		09/25/98	NWD
Nitrite-N	354.1	<0.020	mg/l		09/25/98	NWD
Sulfate	300.0	<1.00	mg/l		09/28/98	JPS
TOC	415.1	<1.0	mg/l		10/01/98	JPS
TDS	160.1	74	mg/l		09/29/98	JEM
METALS						
Aluminum	6010B	<0.050	mg/l	10/02/98	10/08/98	FTS
Arsenic	6010B	<0.005	mg/l	10/02/98	10/08/98	FTS
Barium	6010B	<0.005	mg/l	10/02/98	10/08/98	FTS
Cadmium	6010B	<0.002	mg/l	10/02/98	10/08/98	FTS
Calcium	6010B	0.121	mg/l	10/02/98	10/08/98	FTS
Chromium	6010B	<0.005	mg/l	10/02/98	10/08/98	FTS
Copper	6010B	<0.005	mg/l	10/02/98	10/08/98	FTS
Iron	200.7	<0.100	mg/l	10/02/98	10/08/98	FTS
Lead	6010B	<0.003	mg/l	10/02/98	10/08/98	FTS
Magnesium	6010B	<0.030	mg/l	10/02/98	10/08/98	FTS
Manganese	6010B	<0.010	mg/l	10/02/98	10/08/98	FTS
Mercury	7470A	<0.0001	mg/l	09/30/98	10/01/98	FTC
Nickel	6010B	<0.010	mg/l	10/02/98	10/08/98	FTS
Potassium	6010B	<0.200	mg/l	10/02/98	10/08/98	FTS
Selenium	6010B	<0.005	mg/l	10/02/98	10/08/98	FTS
Silver	6010B	<0.005	mg/l	10/02/98	10/09/98	FTS
Sodium	6010B	0.193	mg/l	10/02/98	10/08/98	FTS
Zinc	6010B	<0.005	mg/l	10/02/98	10/08/98	FTS
Dissolved Copper	6010B	<0.005	mg/l	10/02/98	10/08/98	FTS

USE BALL POINT PEN ONLY, PRESS HARD

GREAT ENVIRONMENTAL SERVICES, INC.
106 Vantage Pointe Drive
Cayce, South Carolina 29033
Telephone No. (803) 791-9700 Fax No. (803) 791-9111

CHAIN OF CUSTODY RECORD

SAMPLE ANALYSIS REQUIRED

CHAIN OF CUSTODY #

Client Name Nevada

Reporting Address McCormick SC

Attention Scott Wilkerson

Telephone No. _____ P.O. No. _____

NPDES # _____

County _____

Receiving Stream _____

Outfall No. _____

Sample ID (Location)	Yr. 1996 DATE	TIME	WELL	SOLID	COMP	GRAB	# of containers	pH, Conductivity	BOD	Nutrients - Specify	METALS - Specify	TOX/TOX - Specify	BTEX	VOC - Specify Method required	Pesticides/PCBs - Specify	Herbicides	Total Phenol	Oil & Grease	BNAs	Solids - Specify	Cyanide	Coliform - Specify type	Toxicity - Specify	General / Dissolved	REMARKS	SESI LAB I.D.
										C	B	C									D			A	N	
GW-1	Start 25Sept									✓	✓	✓									✓			✓	✓	General - Alk, Chloride, N. trate-N, N. trite-N, Sulfate, TDS	147431
	Finish																									
GW-2	Start									✓	✓	✓									✓			✓	✓	Nuts: Ammonia-N Metals - (TOTAL) Al, As, Be	147432
	Finish																									
GW-3	Start									✓	✓	✓									✓			✓	✓	Cd, Ca, Cr, Cu, Pb Mg, Mn, Hg, Ni,	147433
	Finish																									
Well P	Start	1125								✓	✓	✓									✓			✓	✓	K, Sc, Ag, Na, Zn	147434
	Finish																									
Well K	Start	1210								✓	✓	✓									✓			✓	✓	Dissolved Cu	147435
	Finish																									
Well J	Start	1300								✓	✓	✓									✓			✓	✓		147436
	Finish																									
Well H	Start	1320								✓	✓	✓									✓			✓	✓		147437
	Finish																									
Well I	Start 25Sept	1345								✓	✓	✓									✓			✓	✓		147438
	Finish																									

← PRESERVATION (CODE)

CODE: A = None
B = HNO3
C = H2SO4
D = NaOH
E = ICE
F = _____

LAB USE ONLY

Program Area (Circle)
DW CWA/NPDES
RCRA SP/SOL
SP/LIQ Other: _____

SAMPLER Print Name: MILTON QUATTLEBAUM Signature: M. Otm Quattlebaum	Date/Time 25Sept96 1615	Received by (Sig)	Date/Time	Hazards Associated with Sample	Custody Seal Intact (Circle) YES NO NONE
Relinquished by (Sig.)	Date/Time	Received by (Sig.)	Date/Time		Receipt TRC _____ mg/l
Relinquished by (Sig.)	Date/Time	Lab Receipt by (Sig.)	Date/Time 9/25/96 1615		Receipt pH _____ su
					Receipt Temp. _____ °C
					Received on Ice (Circle) YES NO ICE PACK

AMERICAN SYSTEMS, COLUMBIA, S.C.

108 Vantage Pointe Drive
Cayce, South Carolina 29033
Telephone No. (803) 791-9700 Fax No. (803) 791-9111

Page ____ of ____

CHAIN OF CUSTODY #

CHAIN OF CUSTODY RECORD

Client Name: Nevada
Reporting Address: McCormick SC
Attention: S. Wilkerson
Telephone No. ____ P.O. No. ____

NPDES # ____
County ____
Receiving Stream ____
Outfall No. ____

SAMPLE ANALYSIS REQUIRED

Sample ID (Location)	Yr. 1998 DATE	TIME	WELL	SOLID	COMP	GRAB	# of containers	pH, Conductivity	BOD	Nutrients - Specify (C)	METALS - Specify (D)	(OC)TOX - Specify (C)	BTEX	VOC - Specify Method required	Pesticides/PCBs - Specify	Herbicides	Total Phenol	Oil & Grease	BNAs	Solids - Specify	Cyanide (D)	Coliform - Specify type	Toxicity - Specify	General (A)	Dissolved Cu (A)	REMARKS	SESI LAB I.D.
Field Blank	Start 25 Sept / Finish	1336				✓				✓	✓	✓									✓			✓	✓	Gen - Alk, Chloride, TDS, Sulfate, Nitrate-N, Nitrite-N	147439
	Start / Finish																									Nuts - Ammonia-N, TOC	
	Start / Finish																									Metals (TOTAL) Al, As, Ba, Cd, Ca, Cr, Cu, Pb,	
	Start / Finish																									Mg, Mn, Hg, Ni, K,	
	Start / Finish																									Se, Ag, Na, Zn	
	Start / Finish																									Dissolved Cu	
	Start / Finish																										
	Start / Finish																										

←PRESERVATION (CODE)
CODE: A = None
B = HNO3
C = H2SO4
D = NaOH
E = ICE
F = ____

LAB USE ONLY
Program Area (Circle): DW, CWA/NPDES, RCRA, SP/SOL, SP/LIQ, Other: ____

SAMPLER	Date/Time	Received by (Sig.)	Date/Time
Print Name: MILTON QUATTLEBAUM; Signature: Milton Quattlebaum	25 Sept 98 1615		
Relinquished by (Sig.)	Date/Time	Received by (Sig.)	Date/Time
Relinquished by (Sig.)	Date/Time	Lab Receipt by (Sig.) Andy [illegible]	9/25/98 1615

Hazards Associated with Sample

Custody Seal Intact (Circle): YES NO NONE
Receipt TRC ____ mg/l
Receipt pH ____ su
Receipt Temp. ____ °C
Received on Ice (Circle): (YES) NO ICE PACK

Field Data Information Sheet For Groundwater Sampling

Page ____ of ____

Shealy Environmental Services, Inc.
106 Vantage Point Drive
Cayce, S.C. 29033

Date (MM-DD-YY)	**SEPTEMBER 25, 1998**	Casing Diameter: 4 inches	Casing Material: PVC Metal
Field Personnel	**GWS, MPQ**	Guard Pipe: PVC - Metal - No	Locking Cap: Y N
Facility Name	**NEVADA GOLDFIELDS, INC.**	Protective Abutment: Y - No	Integrity Satisfactory: Y - N
Well ID #	GW-1	Well Yield: Low - Mod. - High	
Weather Conditions	Clear Air Temperature °C.	Remarks:	
Total Well Depth (TWD) =	36.95		
Depth To Groundwater (DGW) =	24.95		
Length Of Water Column (LWC) =	12.00		
1 Casing Volume (OCV) = LWC x	.625 .652 = 7.8 gal.		
3 Casing Volumes =	23.4 gal. = Standard Evacuation Volume		
Total Volume of Water Removed =	gal.		
Method of Well Evacuation	TB SSB WW GP Other____		
Method of Sample Collection	TB SSB WW GP Other____		

Evacuation and Collection Methods	Constants for Casing Diameters	
TB - Teflon Bailer	1.5" = 0.092	5" = 1.02
SSB - Stainless Steel Bailer	2" = 0.163	6" = 1.47
WW - Well Wizard	3" = 0.367	7" = 2.00
GP - Grunfos Pump	4" = 0.652	8" = 2.61

FIELD ANALYSES

VOLUME PURGED (GALLONS)	1st	7.8				WELL SAMPLE TIME: 1020
TIME (24 HOUR SYSTEM)	0956	1003				Remarks:
pH (SU)	3.28	3.68				Dry @ 7.8
WATER TEMPERATURE (°C.)	18.0	17.0				
SP. CONDUCTIVITY (UMHOS/CM)	375	380				
TURBIDITY (SUBJECTIVE)*	1	3				
ODOR (SUBJECTIVE)**	1	2				

* 1 = CLEAR 2 = SLIGHT 3 = MODERATE 4 = HIGH

** 1 = NONE 2 = FAINT 3 = MODERATE 4 = STRONG

Field Data Information Sheet For Groundwater Sampling

Page ____ of ____

Shealy Environmental Services, Inc.
106 Vantage Point Drive
Cayce, S.C. 29033

Date (MM-DD-YY)	**SEPTEMBER 25, 1998**	Casing Diameter: 4 inches	Casing Material: (PVC) - Metal
Field Personnel	**GWS, MPQ**	Guard Pipe: PVC - (Metal) - No	Locking Cap: (Y) - N
Facility Name	**NEVADA GOLDFIELDS, INC.**	Protective Abutment: Y - (N)	Integrity Satisfactory: (Y) - N
Well ID #	GW-2	Well Yield: Low - Mod. - High	
Weather Conditions	Clear Air Temperature °C.	Remarks:	
Total Well Depth (TWD) =	28.20		
Depth To Groundwater (DGW) =	22.50		
Length Of Water Column (LWC) =	5.7		
1 Casing Volume (OCV) = LWC x	.652 = 3.7 gal.		
3 Casing Volumes =	11.1 gal. = Standard Evacuation Volume		
Total Volume of Water Removed =	gal.		
Method of Well Evacuation	(TB) SSB WW GP Other_____		
Method of Sample Collection	(TB) SSB WW GP Other_____		

Evacuation and Collection Methods	Constants for Casing Diameters	
TB - Teflon Bailer	1.5" = 0.092	5" = 1.02
SSB - Stainless Steel Bailer	2" = 0.163	6" = 1.47
WW - Well Wizard	3" = 0.367	7" = 2.00
GP - Grunfos Pump	4" = 0.652	8" = 2.61

FIELD ANALYSES

VOLUME PURGED (GALLONS)	1st	3.7				WELL SAMPLE TIME: 1010
TIME (24 HOUR SYSTEM)	0937	0939				Remarks:
pH (SU)	3.58	3.62				Dry @ 3.7
WATER TEMPERATURE (°C.)	18.0	18.0				
SP. CONDUCTIVITY (UMHOS/CM)	600	650				
TURBIDITY (SUBJECTIVE)*	1	1				
ODOR (SUBJECTIVE)**	2	1				

* 1 = CLEAR 2 = SLIGHT 3 = MODERATE 4 = HIGH

** 1 = NONE 2 = FAINT 3 = MODERATE 4 = STRONG

Field Data Information Sheet For Groundwater Sampling

Page ____ of ____

Shealy Environmental Services, Inc.
106 Vantage Point Drive
Cayce, S.C. 29033

Date (MM-DD-YY)	**SEPTEMBER 25, 1998**	Casing Diameter: 4 inches	Casing Material: (PVC) Metal
Field Personnel	**GWS, MPQ**	Guard Pipe: PVC - (Metal) - No	Locking Cap: (Y) - N
Facility Name	**NEVADA GOLDFIELDS, INC.**	Protective Abutment: Y - (N)	Integrity Satisfactory: (Y) - N
Well ID #	GW-3	Well Yield: Low - Mod. - High	
Weather Conditions	Clear Air Temperature °C.	Remarks:	
Total Well Depth (TWD) =	22.6		
Depth To Groundwater (DGW) =	11.4		
Length Of Water Column (LWC) =	11.2		
1 Casing Volume (OCV) = LWC x 0.652	= 7.3 gal.		
3 Casing Volumes = 21.9	gal. = Standard Evacuation Volume		
Total Volume of Water Removed =	gal.		
Method of Well Evacuation	TB (SSB) WW GP Other_____		
Method of Sample Collection	TB (SSB) WW GP Other_____		

Evacuation and Collection Methods
TB - Teflon Bailer
SSB - Stainless Steel Bailer
WW - Well Wizard
GP - Grunfos Pump

Constants for Casing Diameters

1.5"	= 0.092	5"	= 1.02
2"	= 0.163	6"	= 1.47
3"	= 0.367	7"	= 2.00
4"	= 0.652	8"	= 2.61

FIELD ANALYSES

VOLUME PURGED (GALLONS)	1st	7.3				WELL SAMPLE TIME: 1055
TIME (24 HOUR SYSTEM)	1043	1048				Remarks:
pH (SU)	6.15	6.17				Dry @ 7.3
WATER TEMPERATURE (°C.)	20.0	19.0				
SP. CONDUCTIVITY (UMHOS/CM)	210	205				
TURBIDITY (SUBJECTIVE)*	1	3				
ODOR (SUBJECTIVE)**	1	1				

* 1 = CLEAR 2 = SLIGHT 3 = MODERATE 4 = HIGH

** 1 = NONE 2 = FAINT 3 = MODERATE 4 = STRONG

Field Data Information Sheet For Groundwater Sampling

Page ____ of ____

Shealy Environmental Services, Inc.
106 Vantage Point Drive
Cayce, S.C. 29033

Date (MM-DD-YY)	**SEPTEMBER 25, 1998**	Casing Diameter: 2 inches	Casing Material: PVC - Metal
Field Personnel	**GWS, MPQ**	Guard Pipe: PVC - Metal - No	Locking Cap: Y - N
Facility Name	**NEVADA GOLDFIELDS, INC.**	Protective Abutment: Y (N)	Integrity Satisfactory: (Y) - N
Well ID #	Well H	Well Yield: Low - Mod. - High	
Weather Conditions	Clear, Hot Air Temperature °C.	Remarks:	
Total Well Depth (TWD) =	61.98		
Depth To Groundwater (DGW) =	51.91		
Length Of Water Column (LWC) =	10.07		
1 Casing Volume (OCV) = LWC x	0.163 = 1.6 gal.		
3 Casing Volumes =	4.8 gal. = Standard Evacuation Volume		
Total Volume of Water Removed =	gal.		
Method of Well Evacuation	(TB) SSB WW GP Other_____		
Method of Sample Collection	(TB) SSB WW GP Other_____		

Evacuation and Collection Methods	Constants for Casing Diameters	
TB - Teflon Bailer	1.5" = 0.092	5" = 1.02
SSB - Stainless Steel Bailer	2" = 0.163	6" = 1.47
WW - Well Wizard	3" = 0.367	7" = 2.00
GP - Grunfos Pump	4" = 0.652	8" = 2.61

FIELD ANALYSES

VOLUME PURGED (GALLONS)	1st	1.6	3.2	4.8		WELL SAMPLE TIME: 1320
TIME (24 HOUR SYSTEM)	1308	1310	1312	1314		Remarks:
pH (SU)	5.06	4.70	4.68	4.63		
WATER TEMPERATURE (°C.)	20	20	20	19		
SP. CONDUCTIVITY (UMHOS/CM)	80	80	80	80		
TURBIDITY (SUBJECTIVE)*	1	1	1	1		
ODOR (SUBJECTIVE)**	1	1	1	1		

* 1 = CLEAR 2 = SLIGHT 3 = MODERATE 4 = HIGH

** 1 = NONE 2 = FAINT 3 = MODERATE 4 = STRONG

Field Data Information Sheet For Groundwater Sampling

Page ____ of ____

Shealy Environmental Services, Inc.
106 Vantage Point Drive
Cayce, S.C. 29033

Date (MM-DD-YY)	**SEPTEMBER 25, 1998**	Casing Diameter: 2 inches	Casing Material: PVC - Metal
Field Personnel	**GWS, MPQ**	Guard Pipe: PVC - Metal - No	Locking Cap: Y - N
Facility Name	**NEVADA GOLDFIELDS, INC.**	Protective Abutment: Y N	Integrity Satisfactory: Y - N
Well ID #	Well I	Well Yield: Low - Mod. - High	
Weather Conditions	Clear. Hot — Air Temperature °C.	Remarks:	
Total Well Depth (TWD) =	88.30		
Depth To Groundwater (DGW) =	52.25		
Length Of Water Column (LWC) =	36.05		
1 Casing Volume (OCV) = LWC x	0.163 = 5.9 gal.		
3 Casing Volumes =	17.7 gal. = Standard Evacuation Volume		
Total Volume of Water Removed =	gal.		
Method of Well Evacuation	TB SSB WW (GP) Other____		
Method of Sample Collection	(TB) SSB WW GP Other____		

Evacuation and Collection Methods	Constants for Casing Diameters	
TB - Teflon Bailer	1.5" = 0.092	5" = 1.02
SSB - Stainless Steel Bailer	2" = 0.163	6" = 1.47
WW - Well Wizard	3" = 0.367	7" = 2.00
GP - Grunfos Pump	4" = 0.652	8" = 2.61

FIELD ANALYSES

VOLUME PURGED (GALLONS)	1st	5.9	11.8	17.7		WELL SAMPLE TIME: 1345
TIME (24 HOUR SYSTEM)	1328	1330	1332	1334		Remarks:
pH (SU)	5.19	4.58	4.63	4.55		
WATER TEMPERATURE (°C.)	20.0	21.0	20.0	20.0		Field Blank @ 1336
SP. CONDUCTIVITY (UMHOS/CM)	75	65	65	65		
TURBIDITY (SUBJECTIVE)*	3	2	1	1		
ODOR (SUBJECTIVE)**	1	1	1	1		

* 1 = CLEAR 2 = SLIGHT 3 = MODERATE 4 = HIGH

** 1 = NONE 2 = FAINT 3 = MODERATE 4 = STRONG

Field Data Information Sheet For Groundwater Sampling

Page ____ of ____

Shealy Environmental Services, Inc.
106 Vantage Point Drive
Cayce, S.C. 29033

Date (MM-DD-YY)	**SEPTEMBER 25, 1998**	Casing Diameter: 2 inches	Casing Material: (PVC) - Metal
Field Personnel	**GWS, MPQ**	Guard Pipe: PVC - (Metal) - No	Locking Cap: (Y) - N
Facility Name	**NEVADA GOLDFIELDS, INC.**	Protective Abutment: (Y) - N	Integrity Satisfactory: (Y) - N
Well ID #	Well J	Well Yield: Low - (Mod) - High	
Weather Conditions	Clear Air Temperature °C.	Remarks:	
Total Well Depth (TWD) =	63.90		
Depth To Groundwater (DGW) =	58.65		
Length Of Water Column (LWC) =	5.25		
1 Casing Volume (OCV) = LWC x	0.163 = 0.9 gal.		
3 Casing Volumes =	2.7 gal. = Standard Evacuation Volume		
Total Volume of Water Removed =	gal.		
Method of Well Evacuation	(TB) SSB WW GP Other_____		
Method of Sample Collection	(TB) SSB WW GP Other_____		

Evacuation and Collection Methods	Constants for Casing Diameters	
TB - Teflon Bailer	1.5" = 0.092	5" = 1.02
SSB - Stainless Steel Bailer	2" = 0.163	6" = 1.47
WW - Well Wizard	3" = 0.367	7" = 2.00
GP - Grunfos Pump	4" = 0.652	8" = 2.61

FIELD ANALYSES

VOLUME PURGED (GALLONS)	1st	0.9	1.8	2.7		WELL SAMPLE TIME: 1300
TIME (24 HOUR SYSTEM)	1247	1248	1249	1250		Remarks:
pH (SU)	5.10	5.15	5.12	5.11		
WATER TEMPERATURE (°C.)	20.0	20	19.0	19.0		
SP. CONDUCTIVITY (UMHOS/CM)	70	70	70	70		
TURBIDITY (SUBJECTIVE)*	1	1	1	1		
ODOR (SUBJECTIVE)**	1	1	1	1		

* 1 = CLEAR 2 = SLIGHT 3 = MODERATE 4 = HIGH

** 1 = NONE 2 = FAINT 3 = MODERATE 4 = STRONG

Field Data Information Sheet For Groundwater Sampling

Page ____ of ____

Shealy Environmental Services, Inc.
106 Vantage Point Drive
Cayce, S.C. 29033

Date (MM-DD-YY)	**SEPTEMBER 25, 1998**	Casing Diameter: 2 inches	Casing Material: (PVC) Metal
Field Personnel	**GWS, MPQ**	Guard Pipe: PVC - ~~Metal~~ - No	Locking Cap: (Y) N
Facility Name	**NEVADA GOLDFIELDS, INC.**	Protective Abutment: (Y) N	Integrity Satisfactory: (Y) - N
Well ID #	Well K	Well Yield: Low - Mod. - High	
Weather Conditions	Clear Air Temperature °C.	Remarks:	
Total Well Depth (TWD) =	81.53		
Depth To Groundwater (DGW) =	60.25		
Length Of Water Column (LWC) =	21.28		
1 Casing Volume (OCV) = LWC x .163	= 3.5 gal.		
3 Casing Volumes =	10.5 gal. = Standard Evacuation Volume		
Total Volume of Water Removed =	gal.		
Method of Well Evacuation	TB SSB WW (GP) Other____		
Method of Sample Collection	(TB) SSB WW GP Other____		

Evacuation and Collection Methods	Constants for Casing Diameters	
TB - Teflon Bailer	1.5" = 0.092	5" = 1.02
SSB - Stainless Steel Bailer	2" = 0.163	6" = 1.47
WW - Well Wizard	3" = 0.367	7" = 2.00
GP - Grunfos Pump	4" = 0.652	8" = 2.61

FIELD ANALYSES

VOLUME PURGED (GALLONS)	1st	3.5				WELL SAMPLE TIME: 1210
TIME (24 HOUR SYSTEM)	1145	1148				Remarks:
pH (SU)	6.29	5.89				Dry @ 3.5
WATER TEMPERATURE (°C.)	22.0	20.0				
SP. CONDUCTIVITY (UMHOS/CM)	95	80				
TURBIDITY (SUBJECTIVE)*	2	2				
ODOR (SUBJECTIVE)**	1	1				

* 1 = CLEAR 2 = SLIGHT 3 = MODERATE 4 = HIGH

** 1 = NONE 2 = FAINT 3 = MODERATE 4 = STRONG

Field Data Information Sheet For Groundwater Sampling

Page ____ of ____

Shealy Environmental Services, Inc.
106 Vantage Point Drive
Cayce, S.C. 29033

Date (MM-DD-YY)	**SEPTEMBER 25, 1998**	Casing Diameter: 2 inches	Casing Material: (PVC) - Metal
Field Personnel	**GWS, MPQ**	Guard Pipe: PVC - (Metal) No	Locking Cap: (Y) - N
Facility Name	**NEVADA GOLDFIELDS, INC.**	Protective Abutment: Y - (N)	Integrity Satisfactory: (Y) - N
Well ID #	Well P	Well Yield: Low - Mod. - High	
Weather Conditions	Clear Air Temperature °C.	Remarks:	
Total Well Depth (TWD) =	89.18		
Depth To Groundwater (DGW) =	73.06		
Length Of Water Column (LWC) =	16.12		
1 Casing Volume (OCV) = LWC x	.163 = 2.6 gal.		
3 Casing Volumes =	7.8 gal. = Standard Evacuation Volume		
Total Volume of Water Removed =	gal.		
Method of Well Evacuation	TB SSB WW GP Other_____		
Method of Sample Collection	TB SSB WW GP Other_____		

Evacuation and Collection Methods
TB - Teflon Bailer
SSB - Stainless Steel Bailer
WW - Well Wizard
GP - Grunfos Pump

Constants for Casing Diameters

1.5"	= 0.092	5"	= 1.02
2"	= 0.163	6"	= 1.47
3"	= 0.367	7"	= 2.00
4"	= 0.652	8"	= 2.61

FIELD ANALYSES

VOLUME PURGED (GALLONS)	1st	2.6	5.2	7.8		WELL SAMPLE TIME: 1125
TIME (24 HOUR SYSTEM)	1111	1113	1115	1118		Remarks:
pH (SU)	6.44	6.42	6.01	5.99		
WATER TEMPERATURE (°C.)	21.0	20.0	19.0	19.0		
SP. CONDUCTIVITY (UMHOS/CM)	110	110	100	100		
TURBIDITY (SUBJECTIVE)*	3	3	3	3		
ODOR (SUBJECTIVE)**	1	1	1	1		

* 1 = CLEAR 2 = SLIGHT 3 = MODERATE 4 = HIGH

** 1 = NONE 2 = FAINT 3 = MODERATE 4 = STRONG